

TIOC HOW TO GUIDE

How to enable two-way audio between the camera and phone using the internet

For a Camera-only System

The following guide enables you to set up two-way audio between the camera and phone using the internet on *Wiz Sense* (Series 3) and *Wiz Mind* (Series 5 & 7) camera-only systems.



Examples HFW3549T1-AS-PV

HDW5241TM-ASE

HFW5242H-ZE

HDBW7442H-Z

Series

DH-IPC-HF/HFW/HDW/HDBW3X4X Series

DH-IPC-HF/HFW/HDW/HDBW5X4X Series

DH-IPC-HF/HFW/HDW/HDBW7X4X Series

System Version: V2.800.00AD000.0.R Build Date: 2020-07-29

NB: The firmware version is based on the latest version when this document was created and may slightly differ from future versions, however this will not affect any of the functionality.

TIOC HOW TO GUIDE | Enable two-way audio between the camera & phone using the internet

Step 1: Set the camera.

Log in to the camera, go to **Setting** > **Camera** > **Audio**.



Figure 1: Start from the first page of the camera setup.

Tick the **C Enable** checkbox under Main Steam and Sub Steam to activate. Then, go to "Attribute" and set the Audio in Type as "Mic" and adjust the volume.

	ot secure 192.168.5.65		*)*0:
(a)hua			Live Playback Setting Alarm Logout
✓ Camera	Audio Alarm Audio		
ConditionsVideo	Encode		
> Audio	Main Stream	4	
Network	Z Enable		
⊳ Event	Encode Mode G.711A V		
► Storage	Sampling Frequency 8000		
System	Sub Stream		Setting
Finiomation	C Enable Sub Stream 1		Setting
	Encode Mode G.711A V		
	Sampling Frequency 8000		
	Autipute Autipute Tures Min		
	Noise Eiter		
	Microphone Volume		
	Speaker Volume		
	Default Refresh Save	 6 	

Then, *click* **Save** to save your settings.

Figure 2: Enable the two-way audio function from the camera

TIOC HOW TO GUIDE | Enable two-way audio between the camera & phone using the internet

Step 2: Set the DMSS

Firstly, download, install and run DMSS 💮 on your phone.

Secondly, *click* the \oplus button of "**add devices**" at the top right corner. You can choose to add a device by scanning or typing the serial number, and then enter the user name and password to log in the device.

After entering the related information, you need to choose the type of device. Then enter a name for the device and log in to the device using a Username and Password.

Then, *click* **Save** to save your settings.

	Home	Q	+	<	Add D	evice		<	Add Device	Save
• •	0	SN/Scan			000	(*		Add Mode		P2P
Live Playback	Door	IP/Domain	35	Wireless	less Wired Camera	NVR	DVR/XVR			
		Online Searcl	h	Camera				SN:	6F05752AA0	9B0AA
					 ● ○ 	0	0	Device Name:		IPC
	9 0			IVSS	VTO	Doorbell	Chime	Username:		admin
	P				0			Password:		8 %
	Λ			Access	Alarm Station	Alarm Control Panel				
No device. Pl	ease tap -	+ at the uppe	:r-	Other IPC						
				L26	C26E					

Figure 3: Add a device using DMSS

TIOC HOW TO GUIDE | Enable two-way audio between the camera & phone using the internet

Step 3: You should now see the video from the camera on your phone. *Click* \triangleleft to activate the speaker – you will hear the audio from the location of the camera. Then, *click* \blacklozenge to activate the microphone and your voice will be transmitted and will be heard via the speaker on the camera. You can turn off this function by *clicking* it again.



Figure 4: Successfully add a camera and test the speaker and microphone

*Design and specifications are subject to change without notice.

DAHUA UK & IRELAND Quantum, 60 Norden Road, Maidenhead, Berkshire SL6 4AY Tel: +44 (0) 1628 613 500 sales.UK@dahuatech.com support.UK@dahuatech.com If you still encounter problems operating your Dahua device, please call +44 (0)1628 613 500