

OPTIONS



EUROTECH: EURVC-MCP CONVENTIONAL CALL POINT (100-1010)

The Call Points are a call point that mimics the feel of breaking glass whilst offering the user the benefits and environmental advantages of a re-settable operating element. They are compatible with most conventional fire alarm systems. They are safe to use in areas where glass cannot be used such as food processing plants and leisure centres. As the units can be simply reset they provide an ideal solution for areas that suffer from a high number of false activations such as schools, shopping centres and other public places.

KEY FEATURES

- Unique manual call point that mimics the feel of breaking glass whilst offering the user the benefits and environmental advantages of a resettable operating element.
- Three year guarantee against breakage of polycarbonate in normal use (one year guarantee on electromechanical and electronic components).

Design

- An indicator drops into view at the top of the window on activation.
- The unit is then simply reset with a key and is ready for re-use straight away.
- • Waterproof models available, tested to IP67.

Construction

 Extremely attractive, high value look and feel: glass appearance maintains operator deterrence, whilst a visible warning flag confirms activation.

Installation

- Easy installation due to no glass elements that could be broken or incorrectly fitted.
- Surface mounted, 20mm conduit entry points are provided for ease of installation.
- Current rating 3 Amps 12-24V DC,
- Installation terminal conductor size 0.5mm 2.5mm.
- Operating temperature -20°C (-4°F) to 65°C (149°F).

How It Works

 The MCP uses a simple yet ingenious patented mechanism which consists of a rigid plastic operating element and an over centre spring mechanism. This arrangement provides real action on operation and simulates break glass activation. An activation indicator drops into view at the top of the window after the MCP has been operated. The unit is then simply reset with a key and is ready for reuse straight away. Low profile, heavy-duty terminations. \cdot Optional integral cover can be fitted to prevent accidental activation.

Complete functional test with every activation.

Alternative single pole changeover & double pole versions are also available.

Accessories: Reset Key, Integral Cover



Integral Cover Available

DIMENSIONS

Height (mm)	Width (mm)	Depth (mm)		
RP Flush	87	87	23	
RP Surface	87	87	58	



Denotes an MCP that is fitted with a single pole changeover switch both the normally open and normally closed contacts are easily accessed through the installer terminals as illustrated.

- info@eurotechfire.com
- Г: (+44) 020 3141 0999