

The next-generation



More power. More versatility. Maximum peace of mind.



UK and Ireland only



Open-protocol freedom. Maximum versatility.

When it comes to what's needed for each site, we believe our panels' specifiers and installers know best. That's why our next-generation MxPro 5 is more flexible than ever.

Compatible with the leading wired and wireless protocols, now including Core, our multiprotocol approach puts Advanced customers in complete control.

Creating a safer future





Contents

About Advanced Introducing the Next-Generation MxPro 5 New Basecard MxPro 5 Features MxPro 5 System Diagram MxPro 5 Panels Complete False Alarm Management Fire Panel Software AdvancedLive Sustainability Networking MxPro 5 Parts List Technical Support CPDs and Training







Advanced – Made in the UK. Trusted around the world

At Advanced, we're committed to creating a safer future. We deliver fire protection and life safety solutions that protect people and property in more than 80 countries across the globe.

Our products are shaped by decades of research and development expertise as well as ongoing investment in new technologies. This ensures they provide years of high performance and reliability for ultimate peace of mind.

Everything we deliver is rigorously tested and approved to exacting quality standards – which is why Advanced products are trusted by customers the world over and synonymous with quality, performance and ease of use.





We understand that few fire protection challenges are the same, so as well as our mass-customised ranges, we also offer fully-customised solutions. This flexibility gives you complete control over the functions, format and finish of products to suit your site's unique specification.

We are dedicated to providing excellent service and have an international network of offices and agents to help you access sales support with ease - wherever you are in the world.



In addition, our training and technical services are free of charge to all our direct customers and consistently rated as excellent.

For added reassurance, Advanced is part of the safety sector of FTSE 100 company Halma plc. This global group of life-saving technology companies has a clear purpose to grow a safer, cleaner, healthier future for everyone, every day.



A **Halma** company



M***Pro**⁵ protects...





Introducing the next-generation M^{*}_xPro⁵

For over a decade, the MxPro 5 has been reliably delivering fire safety peace of mind in buildings across the world.

And while the panels' looks and dependability haven't altered, the technology and software driving them have been constantly evolving – keeping them – and you – one step ahead in a fast-changing fire industry.

And now, we're taking another step forward by bringing you our most important improvements yet... This is the open-protocol MxPro 5 you know and trust but with a host of new features including easy Cloud connectivity, our simplest ever programming and our fastest processing power to date. And this next-generation MxPro 5 is even more sustainable too...

Here, you can discover all the benefits of our latest panels and why choosing Advanced puts you at the forefront of fire safety...



MxPro 5 fire panels have been certified by FM Approvals, enabling them to carry the FM APPROVED diamond, one of the most prestigious certification marks in the world.

Our most versatile panel

The upgraded MxPro 5 brings you easy connection to AdvancedLive smart monitoring and management, a sustainable upgrade option for existing systems and a host of other new benefits.



Smart, real-time monitoring and control of your Advanced fire system anytime, anywhere on any device.



Upgraded processor and memory

Faster performance of power-up, configuration download, system monitoring and notifications.



Our MXP-568 loop driver card enables a wider range of features and support for all protocols and the latest devices. These include the Apollo Core protocol-compatible Soteria range.



Improved power supply unit

Easier replacement, improved support for third-party equipment and longer battery life.



Quicker, more intuitive programming

Our new-style ConfigTool provides a muchimproved user experience, easier navigation, support for more complex cause and effect programming, a design checker, and over 10 times quicker transfer of configuration settings (typically under 30 seconds).

Increased configuration options

Support for more complex cause and effect programming with increased point configuration and enhanced logic, using the latest Windows technology.

New basecard, new advantages



The updated basecards for our 1-loop, 2-loop, 4-loop and 8-loop MxPro 5 panels provide a host of new benefits, including easier AdvancedLive connectivity, faster commissioning, a more efficient battery performance and a smoother user experience overall.

Basecard comparison:

	Topic title	Previous 'Gen 1' basecard	New 'Gen 2' basecard
1	AdvancedLive: (UK & Ireland only)	No direct connection to AdvancedLive. Additional hardware required.	Ethernet connection to AdvancedLive for easy access to smart fire system monitoring (UK & Ireland only)
2	Power supply unit:	Integrated into basecard	Upgraded and separate from basecard for easier replacement and integration with third-party equipment
	Menu navigation:	Limited menu navigation responsiveness	Improvements to menu navigation support quick and easy installation and commissioning
3	Configuration software:	Not forward compatible with next-generation basecard. Uses PC-Net-003 configuration software	Uses PC-Net-022 which has an improved user interface and navigation, including improved cause and effect and backwards compatibility
	Download time:	Panel/PC average download time of 4 minutes	Connection to PC is much faster – less than 30 seconds
4	Memory:	Memory size limited to 512KB x 8	Enhanced memory size 1MB x 8 (4 x greater memory capacity) provides improved capabilities and functionality and supports larger fire systems
	Number of points:	1000	2000
	Input events:	250	2000
	Logic terms:	1500 Apollo/Hochiki 500 Argus and Nittan	2000
	Logic statements:	100	250
	Logic lines:	1500 Apollo/Hochiki 500 Argus and Nittan	3000
	Output group lines:	1150	2000
5	Chassis for simple and easy upgrade and replacement:	Basecard mounted on chassis plate for easy removal/retrofit	Easy replacement of the basecard allows more sustainable, cost- effective upgrade of existing MxPro 5 panels to next-generation model

Chassis for simple and easy upgrade and replacement 5

- · Basecard mounted on chassis plate for easy removal/retrofit
- Allows more sustainable, cost-effective upgrade of existing MxPro 5 panels to next-generation model

M*Pro⁵ More power. More versatility. Maximum peace of mind.

The next-generation MxPro 5 combines valuable new features with the familiar benefits that have made this panel so versatile and popular.

Our open protocol flexibility:

- Gives you the freedom to match the bestperforming panel with the most appropriate detector range for the site
- Means no tie-ins to expensive maintenance contracts and restrictive agreements
- Includes intuitive programming, powerful networking, comprehensive cause and effect, false alarm reduction and unique diagnostic features that put you in complete control of your fire protection for total fire safety peace of mind.

Ċ

Easy to install and use

MxPro 5 panels are EN54-approved and simple to install, configure and use.

- Easy-fix removable chassis and in-built software make MxPro 5 fire panels simple to set up
- Powerful networking, extensive configuration options and comprehensive cause and effect put you in complete control
- Intuitive menus, with simple click-and-select programming, for simple, easy commissioning
- Support for intelligent remote terminals, I/O drivers and BMS interfaces make light work of connecting with building management systems
- Help, advice, tips and training are all on hand from our experienced technical support team. We also have an extensive collection of 'how to' videos on our YouTube channel.

Our proven fire protection:

- Is fully approved to EN54 Parts 2 and 4
- Is suitable for use across a wide range of locations

 whether networked to protect hospital complexes and large public transport systems, used in combination with building management systems in high-rise commercial developments or chosen to safeguard historical artefacts in historic settings
- Offers a reliable, scalable solution, backed up by lifetime technical support.



Scalable and versatile

We know that sites can expand, and fire protection requirements change and evolve over time. That's why we've designed MxPro 5 to be scalable and versatile, able to adapt as required with minimal fuss or disruption.

- Standalone one, two, four or eight loop formats let you choose the panel size that meets your requirements and budget
- A choice of remote display terminals includes TouchControl – our 10-inch touchscreen with interactive maps and zone plans ideal for public reception areas
- Up to 254 devices per loop (depending on chosen protocol) and an overall capacity of over 200,000 devices per network
- Every panel is networkable with up to 200 network nodes and 2,000 fire detection zones
- Panels can support wired and wireless loops, or a hybrid of both (depending on chosen protocol)
- Compatibility with a choice of leading detector partners – Apollo, Argus, Hochiki and Nittan to suit your exact needs.

Packed with premium features

Every MxPro 5 panel comes with a host of advanced features built in as standard, giving you peace of mind that you won't need to buy expensive add-ons in the future.

- Unique diagnostic features include 'scope on board' to provide panel readings from any loop, making it easy to identify and investigate issues
- Network diagnostic tool helps prevent fires and faults from being transmitted across the network
- Built-in multimeter measures all voltages and currents across the system, so you can speed up the commissioning process by identifying voltage/ current levels in real time
- Every panel includes AlarmCalm false alarm management software to help you minimise unwanted alarms, with 200 programmable false alarm management 'building areas' per panel
- Ability to monitor the circuit from any panel or remote terminal and see a complete device history on every panel
- Standard peripherals include direct USB and RS232 PC connections, and peripheral expansion is built in for added peace of mind
- 20 built-in, fully programmable LEDs as standard without the need to buy a separate LED zone card
- On-board or optional remote battery temperature sensor ensures optimum operational efficiency and life
- 4 programmable push buttons on the front of the panel for user customisation according to the fire system's needs
- 5,000 event and diagnostic, and 500 fire event log entries, for comprehensive tracking and auditing
- Timed enablement of disabled zones, input and output devices, to program and manage fire system response and reporting
- Modular in construction, with mass customisation options including the ability to program your own company logo to appear on the fire panel screen.



Powerful, flexible service reporting

Every MxPro 5 panel includes an inbuilt, easy-to-use, Windows-based service tool which saves you time and money by providing easy, instant access to historic and real-time device data, and shows proof of servicing at a glance.

- Download service reports, inspect the device history and keep track of service schedules for safety audit compliance
- Customisable data filters make it easy to focus on potential trouble spots and ensure they're checked and tested during servicing
- Predict which devices are becoming contaminated so you can clean/replace them before they cause a false alarm
- Customise reports to show the data you need and export it as PDF, Excel or HTML files to prove compliance simply and efficiently.



M***Pro⁵ Features**

Hardware Features	
Display backlight	White backlit display
	Improved efficiency with programmable dimming options
	Software-driven contrast adjustment via menu
PC connections	USB and RS232 – independently operated
Peripheral expansion bus	Built in as standard on all panels
	Extended range of P-Bus option cards
Wiring fault monitoring	EN54-2: Open circuit, short circuit
	EN54-13: Continuous checking for increases in resistance, (loose terminations), partial shorts etc.
Control keys	Mute, Silence, Reset, LED Test, Resound, Evacuate and dedicated More Alarms buttons on control panels and large repeater
	Configurable keypad repeat keys
Front panel push buttons	4 programmable function buttons on control panels and large repeater
Battery charging	Charger current (up to 2 amps), voltage and temperature available from any display on a network
	Built-in or remote battery temperature sensor
Zone LEDs	20 integral red LED indicators included as standard on control panels and large repeater Can be assigned to any fire zone or programmable for other uses
	Up to 200 additional LEDs with Large, Deep and Extended enclosures. (Up to 50 in Medium enclosure) Options include red, yellow and (bi-colour) red/yellow or green/yellow column format with slide-in labels
Programmable input	Dedicated monitored switch input as standard on all panels
Programmable key switch inputs	Built-in as standard on all panels
Printer	Optional on-board printer. No additional battery pack required. Integral paper feed button. Printer fault conditions displayed on panel, prints customer logo
Power	Aux supply output @ 500mA 24V
Standards	Approved to EN54 Parts 2 and 4
Software Features	
Dedicated output connection (via	Removes the need for additional BIMS connections/hardware
Ethernet port) for AdvancedLive*	Easy to set up and simplifies managing and monitoring your fire system, no matter where you are
Independent general event and fire	Yes – on all panels and repeaters
event logs	Any panel can be configured as a network-wide main event log
Event log entries	5,000 + 500 fire
	Additional logging for investigation delays and any enable/disable actions
Timed disable options	Permanent or automatic timed re-enablement of any input or output device
Enable/disable inputs by zone	All inputs
	Selected inputs
	Only automatic inputs
	Only manual inputs
	All other inputs
Enable/disable outputs	Disable by output purpose
	Configurable disable outputs menu options include: sounders, relays, beacons, fire routing, fault routing, fire protection, pager, all or selected
	Disablement of outputs across network configurable by sector mask
Real-time clock	Yes - no lithium battery required
Languages	Supports multiple different character sets (code pages) and languages

Network Features	
Network Features	200,000
Max devices per network	200,000
Max nodes on network	200
Sectors	200
Maximum fire zones displayed	2,000 on all panels
Programming Features	
Independent building areas for false alarm management	201 areas per panel
	Local or global alarm acknowledgement faci
Zone LEDs	All LEDs fully programmable
	PC configuration presented graphically Primary/secondary activation
Buzzer options	Smart latch of faults
	Fault notification can resound daily
	Service option to inhibit by time clock
Programmable input actions	22 – including new supervisory, fire routing
Output purpose	Output purpose configurable
Output ringing styles	40 – output activation priority configurable
Zone qualifiers	24 categories of zone qualifiers
Logic statements	3,000 logic lines – programmable options:
	Inputs
	Any 2 inputs
	Zone qualifiers
	Any 2 zones
	General events
	Time clocks
General events	36 categories
Blocking rules	Programmable blocking rules – by general e
Service and Diagnostic Features	
Device history	For every device the time and date of the:
	Last activation
	Last test Last disable
	Last disable Last enable
	Date created
On-board digital storage scope	Yes
View panel voltages and currents	Available from any MxPro 5 repeater or pan
View panel status	View status of all panel circuits across netw
	Firmware version of all internal hardware ar
Firmware updates	All hardware flash upgradable via panel US
Detector status information	a fault level is reached
Detector status information	
	a fault level is reached
Detector status information	a fault level is reached Download device information
Detector status information	Download device information Extract event log information

		×		
20	I		I	t\/
10	I	I.	ı	ιy
				~

ing and fire protection confirmed + alarm acknowledgement actions

l event or output groups

panel on the network

etwork

e and peripheral devices can be viewed at the panel

JSB or serial port

earing drift contamination limits to be identified during routine servicing before

tors

M**XPro⁵ System diagram**



M^{*}_xPro⁵ Options

1 Loop



options AdvancedLive ready

Single loop

Small enclosure

Maximum 7Ah internal batteries

Optional programmable key switch

Medium, large and deep enclosure

• 20 programmable LEDs

Programmable input

1-2 Loop



 Up to 50 additional programmable LEDs • Up to 8 programmable key switches

for a 2-loop panel

Medium enclosure

or 4 plus printer

Maximum 12Ah internal batteries

Order an extra loop driver card

- Plexi-glass door option
- Large and deep enclosure options
- AdvancedLive ready

2-8 Loop



Integrated Peripheral Bus

· Peripheral expansion option cards include:

4-way relay card

4-way sounder card

- 10-way relay card

- Redundant controller

· Rack-mountable control panels

Dedicated mimic door option

Rack Mount

- 10-way monitored input card

+ 3 programmable relays)

- 16-way push button/48 LED card

- Fire and fault routing/protection card

• Additional 16U and 20U high IP55 enclosures

• Rack-mount peripheral chassis plate, LED and switch-card module options

• Integrated P-Bus as standard on all MxPro 5 panels

• Up to 32 expansion cards can be added to an MxPro 5 panel

- Conventional zone card (8 class B or 4 class A zones

- 16-way input/48 output (direct drive LED outputs)

1-4 Loop

- Order an extra loop driver card for a 2-loop panel, 2 cards for a 3-loop panel and 3 for a 4-loop panel
- Large enclosure
- Maximum 17Ah internal batteries
- Up to 200 additional programmable LEDs Up to 8 programmable key switches or 4 plus printer
- Plexi-glass door option
- Deep and extended enclosure options
- AdvancedLive ready



- Order an extra loop driver card for a 2-loop panel, 2 for a 3-loop panel, 3 for a 4-loop panel etc Extended enclosure
- Maximum 45Ah internal batteries Up to 200 additional programmable
- LEDs, 2 x switch cards or mimic Up to 8 programmable key switches or 4 plus printer
- Plexi-glass door and external battery box option
- AdvancedLive ready

Remote Terminals

- Four types available:
- TouchControl 10" touchscreen with active maps and zone plans, plus a customisable home screen for your logo or promotional presentations
- Remote display terminal
- Remote control terminal with additional mute, silence, reset _ and resound keys
- Remote control terminal with additional LED status indication. four programmable push buttons, mute, silence, reset, resound, lamp test and evacuate keys
- Optional level 2 access enable key switch (not TouchControl)
- · Integrated standard or fault-tolerant network interface with screen termination point
- Programmable display for up to 2,000 zones along with sectorbased controls





AlarmCalm Complete False Alarm Management.

MxPro 5 features the power and flexibility of our in-built AlarmCalm false alarm management and reduction software.

This is unique in the UK in offering a solution to false alarms that meets the requirements of BS EN54-2.

Clauses 7.11 & 7.12 in that standard are often referred to as dependencies, verification delays, investigation delays or delays to outputs.

AlarmCalm uses fast hardware, powerful software and optional, intelligent loop devices to build a total solution to false alarms that's versatile and easy to configure. You can design a solution around the needs of your specific site and this can radically reduce the disruption, inconvenience and costs associated with unwanted alarms.

Optional verification button



This is an intelligent verification device that can be installed on the loop and works with the AlarmCalm software to allow occupants to acknowledge a fire alarm signal locally, if they believe it has been triggered accidentally.

16

AlarmCalm features:

Versatile cause and effect

In-depth control over alarm verification and investigation delays to outputs.

Customised management for any site

Divide your building(s) into 'building areas', each with guick-to-apply unique or group false alarm management settings. 50 building areas per panel.

Unlimited points

No restriction on the number of points in a building area and configurable by point.

Global acknowledgement

Panel inputs can be programmed to manage verification and output delays.

Flexible verification

Options include: set verification by building area, day/night, on/ off, change verification times, verification by second device or device mode change.

• Full event log

All verification and output delays recorded in panel event logs.

Multiple verification inputs and outputs

Inputs can include optical, heat and multisensors, callpoints and AlarmCalm button or other input modules. Outputs can be sounders, beacons and relays etc. Sounder ring styles can be configured.

Failsafe operation

Total control over verification times. Users can only extend verification once. Set maximum number of areas in verification before full fire is signalled.

Easy management of outputs

Output delays are handled in exactly the same way as verifications, making setup very simple.

AlarmCalm is not compatible with Apollo Core protocol.



Scan the QR code to find out more about AlarmCalm

Our most intuitive configuration software yet

The next-generation MxPro 5 uses our latest ConfigTool, (PC-Net-022) – for faster, more flexible, fuss-free setup.



Improved user interface

e

1 Loop grid with right-hand panel for settings/selections by device

- We've updated the user interface with speed and efficiency in mind. You can access most operations from the program menu, aided by a toolbar with descriptions of each function and easy-to-follow icons.
- We've also optimised the use of the available screen space to ensure more information is visible. You can see all the devices fitted by address in a grid layout. Simply by selecting an address, you can configure all device inputs and outputs from the same screen.



te Product Check Design (Product Check Design (Pro	ommunications Help Quant Logic A Groups	d Renove Change	Cut Cut	Export Quick Che Edit an	Cause d lifted und Debut	- •
ator	Panel 1 > Loop 1	00	9 📫	ġ		Point Details
Famil Upoat Regured On-Board User Interface	1 MOP		2 3 Heat		21 5	Address La Type Call Fort Lasten Text Zhre I Dout form Pre Pre Pre Report Category A
Pegheral Bus Loop 1			8	5	10	Double Knock Berk On Pal Dealement Graup SSMTIme Dock No Unused ISSMTIME Dock No Unused
	11	12	13	14	16	Delay (0) 0
	16	17	18	19	20	
	21	22	23	24	26	
	26	27	28	29	30	





Notice (12) Notice (12) Notice (12) Image: Notice (12)</t

Fast communication

- Communication speed is greatly improved. Transfer of the configuration settings to/from the panel is more than 10 times faster than previously – typically taking just 30 seconds instead of 6 to 8 minutes.
- Super-fast file loading and saving saves you time and money, even when working with large, complex site designs.
- You can now import from another design and choose from more settings than ever before. Plus, to ensure seamless working between existing and new MxPro 5 installations, you can import files from PC-Net-003.

Versatile software

In addition to the ConfigTool, you have access to a range of other software designed to make the setup and use of MxPro 5 panels fast, efficient and flexible.

We are continually developing our software for the MxPro 5 panel range, adding new features and performance enhancements.

Our position in the global fire industry means we help guide legislation and can implement software changes quickly, keeping our systems right up to date. We also listen closely to our customers and often produce features for specific client requirements.

LogoTool

- Allows the installer's logo to be displayed on the panel's graphical LCD display during normal operation
- Uploads standard bitmap images
- Tool allows creation of logos
- · JPG and GIF images can be imported



ServiceTool

- · Extract device information and event logs from single or multiple panels
- · Device history including last activation, test, enable, disable and date created
- · User-defined filters allow data to be grouped and searched in many different ways
- · View device status, analogue values and drift (contaminated) information
- · Network simulation and test feature
- Categorise events and create user-defined reports



TerminalTool

- Now part of PC-Net-022
- · Virtual panel display supports remote interrogation
- Direct USB/RS232 or remote modem/IP connection
- Real-time status information and control
- TerminalTool (PC-Net-004) is no longer available



MapApp

- · Used to easily add site maps to TouchControl touchscreen repeater
- · Can use any illustration from a photo to a line drawing, isometric or plan
- · Simply draw hotspots onto drawing to add fire zones
- · Export to microSD card to add to TouchControl RCT



M^{*}**Pro**⁵



Advanced Performance. Wireless Versatility.

Compatible with leading detector protocols

ooking for a flexible range	
of wireless fire safety	
solutions you can trust?	
ook no further than	,

Creating a safer future

Advanced – made in the UK. Trusted around the world.

Advanced.

Contact us to discuss your wireless fire safety requirements: advancedco.com | enquiries@advancedco.com | +44 (0)345 894 7000

*subscription cost applies



Whether you need a fast-fit fire system upgrade, wired and wireless hybrid adaptability, or versatile fire panels compatible with the leading wireless protocols, Advanced brings you fire safety peace of mind.



Advanced

Want Advanced fire safety peace of mind?



Easy connectivity to AdvancedLive monitoring

With the next-generation MxPro 5, it's now easier than ever to access the benefits of AdvancedLive, whether you're creating a new network or upgrading an existing one.



The next-generation MxPro 5 brings you secure, easy, real-time management, of your fire system – anytime, anywhere, on any internetenabled device.

Connection is simple using the Ethernet port on the panel.

Once set up, the clear dashboard simplifies day-today monitoring, while instant alerts flag fires, faults and fixes – fast.

Book a demo today to discover a new level of fire safety confidence and control with AdvancedLive

Email: enquiries@advancedco.com

Find out more

Scan this QR code to find out more about AdvancedLive including:



qrco.de/Advlive

- 2-minute overview film
- How AdvancedLive will help you
- Information for IT managers about the security of AdvancedLive

FAQs



Advanced – made in the UK. Trusted around the world. Discover more: advancedco.com | enquiries@advancedco.com | +44 (0)345 894 7000



For help with upgrad



For help with upgrading your existing networks of 'Gen1' MxPro 5 panels to enjoy 'Gen2' next-generation benefits, please contact customerservices@advancedco.com



We are committed to 'creating a safer, sustainable future', both in our own right, and as a member of Halma plc, a FTSE 100 company with a shared purpose to 'grow a safer, cleaner, healthier future for everyone, every day'.



As part of our commitment to sustainability, we are working hard to find ways to reduce our environmental impact. We choose environmentally friendly methods of manufacture wherever possible and actively seek out more sustainable ways of operating across our business.

In upgrading our MxPro 5 range, we have incorporated elements of sustainable design to make it easy for you to benefit from nextgeneration features on existing Advanced systems - simply by swapping basecards.



We are an ISO 14001 accredited company, dedicated to reducing our impact on the environment.

How to swap basecards:

Mounted on an easy-fit chassis plate, it is a straightforward process for trained engineers to switch the basecard, avoiding the need to replace entire hardware installations.



Find out more about our sustainability work Visit our website or scan this QR code





Advanced networking

Our high-performance network technology works across the MxPro 5 range, delivering the easiest setup and best-performing fire panel networks available.

Easy connection

- Connect all MxPro 5 control panels, remote terminals and network peripherals together using fire-resistant, two-core cable
- Distribute panels throughout the building for lower wiring costs
- Caters for the smallest two-panel network through to the largest 200 panel, wide-area, networked system
- Simply add and connect a network card to any MxPro 5 control panel or remote terminal

Peer-to-peer system

- Does not rely on a single 'master' panel to function
- Information from any input or output device can be passed over the network and displayed on any MxPro 5 control panel or remote terminal
- Details include fire, general alarm, pre-alarm, fault, control inputs and disablement



Type of network	Standard	Fault tolerant	
Typical use	Sites where one panel per building controls evacuation	Sites where more than one panel per building controls evacuation	
Setup	Standard network card: MXP-503	Fault-tolerant network card: MXP-509	
Maximum cable length	Up to 1.5km	Up to 1.5km between nodes	
No. of nodes	32 (50 with signal buffer)	200	
No. of zones	2,000	2,000	
Typical time to communicate first event	1 second	3.5 seconds	

AdvancedLive is available in the UK and Ireland only

Zoning

- Networked systems can share up to 2,000 zones
- Autolearning the devices, adding text and assigning zone numbers is easy
- · All other nodes on the network are instantly aware of a panel as soon as it is given a valid network node address

Diagnostic and status information

- All panels provide valuable diagnostic and status information and have the facility to prevent the transmission of fires or faults during commissioning
- Intuitive software enables easy configuration of complicated cause and effect for more complex systems
- · All configuration data is contained within one userfriendly network configuration file

M***Pro⁵ Parts list**

Product Code	Description	
	Apollo & Hochiki Protocols	
MX-5101	1-Loop Fire Panel – small enclosure	
MX-5101M	1-Loop Fire Panel – medium enclosure	
MX-5101L	1-Loop Fire Panel – large enclosure	
MX-5101D	1-Loop Fire Panel – deep enclosure	
MX-5201	1-2 Loop Fire Panel c/w 1 Loop Card – medium encl.	
MX-5201L	1-2 Loop Fire Panel c/w 1 Loop Card – large encl.	
MX-5201D	1-2 Loop Fire Panel c/w 1 Loop Card – deep encl.	
MX-5401	1-4 Loop Fire Panel c/w 1 Loop Card – large encl.	
MX-5401D	1-4 Loop Fire Panel c/w 1 Loop Card – deep encl.	
MX-5401E	1-4 Loop Fire Panel c/w 1 Loop Card – extended encl.	
MX-5802	2-8 Loop Fire Panel c/w 2 Loop Cards – extended (standard network)	
MX-5802/FT	2-8 Loop Fire Panel c/w 2 Loop Cards – extended (fault-tolerant network)	
All 2-, 4- and 8-Loop panels are available with up to 2, 4 & 8 Loop Cards fitted		

	Apollo Core Protocol
MX-5101A	1-Loop Fire Panel – small enclosure
MX-5101AM	1-Loop Fire Panel – medium enclosure
MX-5101AL	1-Loop Fire Panel – large enclosure
MX-5101AD	1-Loop Fire Panel – deep enclosure
MX-5201A	1-2 Loop Fire Panel c/w 1 Loop Card – medium encl.
MX-5201AL	1-2 Loop Fire Panel c/w 1 Loop Card – large encl.
MX-5201AD	1-2 Loop Fire Panel c/w 1 Loop Card – deep encl.
MX-5401A	1-4 Loop Fire Panel c/w 1 Loop Card – large encl.
MX-5401AD	1-4 Loop Fire Panel c/w 1 Loop Card – deep encl.
MX-5401AE	1-4 Loop Fire Panel c/w 1 Loop Card – extended encl.
MX-5802A	2-8 Loop Fire Panel c/w 2 Loop Cards – extended (standard network)
MX-5802A/FT	2-8 Loop Fire Panel c/w 2 Loop Cards – extended (fault-tolerant network)

All 2-, 4- and 8-Loop panels are available with up to 2, 4 & 8 Loop Cards fitted

	Argus Protocol
MX-5101V	1-Loop Fire Panel – small enclosure
MX-5101VM	1-Loop Fire Panel – medium enclosure
MX-5101VL	1-Loop Fire Panel – large enclosure
MX-5101VD	1-Loop Fire Panel – deep enclosure
MX-5201V	1-2 Loop Fire Panel c/w 1 Loop Card – medium encl.
MX-5201VL	1-2 Loop Fire Panel c/w 1 Loop Card – large encl.
MX-5201VD	1-2 Loop Fire Panel c/w 1 Loop Card – deep encl.
MX-5401V	1-4 Loop Fire Panel c/w 1 Loop Card – large encl.
MX-5401VD	1-4 Loop Fire Panel c/w 1 Loop Card – deep encl.
MX-5401VE	1-4 Loop Fire Panel c/w 1 Loop Card – extended encl.
MX-5802V	2-8 Loop Fire Panel c/w 2 Loop Cards – extended (standard network)
MX-5802V/FT	2-8 Loop Fire Panel c/w 2 Loop Cards – extended (fault-tolerant network)
All 2-, 4- and 8-Loop pane	Is are available with up to 2, 4 & 8 Loop Cards fitted

Product Code	Description	
	Nittan Protocol	
MX-5101N	1-Loop Fire Panel – small enclosure	
MX-5101NM	1-Loop Fire Panel – medium enclosure	
MX-5101NL	1-Loop Fire Panel – large enclosure	
MX-5101ND	1-Loop Fire Panel – deep enclosure	
MX-5201N	1-2 Loop Fire Panel c/w 1 Loop Card – medium encl.	
MX-5201NL	1-2 Loop Fire Panel c/w 1 Loop Card – large encl.	
MX-5201ND	1-2 Loop Fire Panel c/w 1 Loop Card – deep encl.	
MX-5401N	1-4 Loop Fire Panel c/w 1 Loop Card – large encl.	
MX-5401ND	1-4 Loop Fire Panel c/w 1 Loop Card – deep encl.	
MX-5401NE	1-4 Loop Fire Panel c/w 1 Loop Card – extended encl.	
MX-5802N	2-8 Loop Fire Panel c/w 2 Loop Cards – extended (standard network)	
MX-5802N/FT	2-8 Loop Fire Panel c/w 2 Loop Cards – extended (fault-tolerant network)	
All 2-, 4- and 8-Loop panels are available with up to 2, 4 & 8 Loop Cards fitted		

	Loop Driver Cards	
MXP-568	Loop Driver Card – Apollo (incl Core protocol), Hochiki, Argus	
MXP-567	Loop Driver Card – Nittan	
	Remote Terminals	
MX-5010	Remote Display Terminal (RDT)	
MX-5020	Remote Control Terminal (RCT) – small	
MX-5030	Remote Control Terminal (RCT) – large	
MX-5010/FT	Remote Display Terminal (RDT) – fault tolerant	
MX-5020/FT	Remote Control Terminal (RCT) – small (fault tolerant)	
MX-5030/FT	Remote Control Terminal (RCT) – large (fault tolerant)	
	TouchControl	
TOUCH-10	Touch-Screen Terminal – standard network	
TOUCH-10/FT	Touch-Screen Terminal – fault-tolerant network	
TOUCH-10-SBB	Touch-Screen Terminal Surface Back Box	

	Network Cards
MXP-503*	Network Card – standard network
MXP-509*	Network Card – fault-tolerant network
MXS-028	Spare Fault-tolerant Network Interface
MXP-030	Standard Network Booster/Isolator - DIN-rail module
MXP-542	24VDC – 24VCD Converter/Isolator
MXP-635-A	Fibre Optic Converter – active
MXP-635-P	Fibre Optic Converter – passive
MXP-635-MM	Fibre Optic Converter Multi-Mode
MXP-635-SM	Fibre Optic Converter Single-Mode
MXP-635-BD/AB	Fibre Optic SFP Module – bi-directional (up)
MXP-635-BD/BA	Fibre Optic SFP Module – bi-directional (down)
MXP-635/IVIEW	Fibre Optic iView Commissioning Tool (limited)
MXP-635/COMM	Fibre Optic iView Commissioning Tool (interactive)
* Add F for fitted	

Product Code	Description	Product Code	Description
	Peripherals & P-Bus Expansion Cards		LED Indication
MXP-034*	4-Way Sounder Card	MXP-513M-050RD*	50 Zone Fire (red)
MXP-035*	4-Way Relay Card	MXP-513M-050RY*	50 Zone Fire (red) + Fault (yellow)
MXP-035-BXP	4-Way Relay Card with 1.5A PSU – boxed	MXP-513M-050YL*	50 Zone Fault (yellow)
MXP-506	Routing Termination Card	MXP-513L-050RD*	50 Zone Fire (red)
MXP-532*	Routing/Protection Interface	MXP-513L-050RY*	25 Zone Fire (red) + Fault (yellow)
MXP-536*	8-Way Conventional Zone Monitor Card	MXP-513L-050YL*	50 Zone Fault (yellow)
MXP-537*	10-Way Monitored Input Card	MXP-513L-100RD*	100 Zone Fire (red)
MXP-538	Switch/LED Module – 16 switches, 3 programmable	MXP-513L-100RY*	50 Zone Fire (red) + Fault (yellow)
	LEDs/switches (red, yellow, green)	MXP-513L-100YL*	100 Zone Fault (yellow)
MXP-539	Multi-Way I/O Mimic Driver Card – 16 switch inputs	MXP-513L-200RY*	200 Zone Fire (100 x red) + Fault (100 x yellow)
	and 48 LED outputs	MXP-513L-050CRY*	50 Zone Column Format – Fire (red) + Fault (yellow)
MXP-544*	8-Way Relay Card	MXP-513L-050CRYG*	50 Zone Column Format (30 x red/yellow and
Add F for fitted			20 x green/yellow)
	Other Peripherals	MXP-513-050RD*	50 Zone Fire (red)
MXP-501	Remote Battery Temperature Sensor	MXP-513-050RY*	25 Zone Fire (red) + Fault (yellow)
MXP-505	Sounder (Pt13) Active EOL	MXP-513-050YL*	50 Zone Fault (yellow)
MXP-507*	2-Way Relay Card	MXP-513-100RD*	100 Zone Fire (red)
MXP-512*	Printer Assembly	MXP-513-100RY*	50 Zone Fire (red) + Fault (yellow)
MXS-509	Spare Paper Roll for MXP-512 Printer	MXP-513-100YL*	100 Zone Fault (yellow)
MXP-053	2-Way Stretch/Latch Input Module	MXP-513-200RY*	200 Zone Fire (100 x red) + Fault (100 x yellow)
* Add F for fitted		MXP-513-050CRY*	50 Zone Column Format – Fire (red) + Fault (yellow)
Add 1 for filled	AlarmCalm	MXP-513-050CRYG*	50 Zone Column Format (30 x red/yellow and 20 x green/yellow)
MXP-541A-002	AlarmCalm Button with Buzzer – Apollo (not supported	* Add F for fitted	
	for Core protocol)		
MXP-541V-002	AlarmCalm Button with Buzzer – Argus		BMS Interface
		MXP-510-BX	BMS/Graphics Interface – boxed
	Key Switches	MXP-510-BX/FT	BMS/Graphics Interface – boxed (fault tolerant)
MXP-511*	Access Enable Key Switch for 5000	MXP-510	BMS/Graphics Interface – card only
MXP-518-001*	Access Enable Key Switch for 5010/5020	MXP-510/FT	BMS/Graphics Interface – card only (fault tolerant)
MXP-518-002*	Access Enable Key Switch for 5030	MXP-642	Commander-BACnet/Modbus (IP) Interface (Standard, Basic) – requires BMS-510
MXP-516*	2-Pos Key Switch – trapped	MXP-642C	Commander-BACnet/Modbus (IP) Interface (Configure
MXP-517*	2-Pos Key Switch – untrapped		- requires BMS-510
MXP-519*	2-Pos Key Switch – momentary (trapped)	23-PSU/250	Commander Power Supply – 12VDC 2.5A
MXP-515*	3-Pos Key Switch – untrapped all positions		
MXP-515T*	3-Pos Key Switch – key-free in centre position only		Graphics Software
MXS-511-KEY	Spare MXP-511 Access Enable Key	PC-NET-005-L1	Graphical Control Software – standard (up to 3 panels
* Add F for fitted		PC-NET-005-L2	Graphical Control Software – standard (up to 15 pane
	Network Peripherals	PC-NET-005-L2P	Graphical Control Software – premium (up to 15 panels)
MXP-545	PENN – standard network	PC-NET-005-L3	Graphical Control Software – standard (up to 200
MXP-545/FT	PENN – fault-tolerant network		panels)
MXP-046	Damper Interface Module (Apollo protocol)	PC-NET-005-L3P	Graphical Control Software – premium (up to 200
MXP-046-BX1 MXP-547*	Damper Interface Module – boxed (Apollo protocol)	DO NET OOF OWNA	panels)
	ESPA Pager Interface	PC-NET-005-SWM	Smart Watch Module
MXP-547-BX	ESPA Pager Interface – boxed	PC-NET-005-SWM4R	Smart Watch Module (4 inputs)
* Add F for fitted		PC-NET-005-SWM6	Smart Watch Module (4-6 panels)
		PC-NET-005-SWM15	Smart Watch Module (7-15 panels)
		PC-NET-005-SCU	Smart Cube Unit
		PC-NET-005-L1R-L2R	Dongle Upgrade L1R to L2R
		PC-NET-005-L2R-L3R	Dongle Upgrade L2R to L3R
		PC-NET-005-L2R-L2P	Dongle Upgrade L2R to L2P
		DO NET OOF LOD LOD	
		PC-NET-005-L2P-L3P	Dongle Upgrade L2P to L3P Dongle Upgrade L3R to L3P

M***Pro⁵ Parts list**

Product Code	Description		
	Cables		
UP-001	FS232 9-Way to 3-Way Plug-In Connector – upload/ download lead		
UP-006	USB Upload/Download Lead for Config Software		
UP-015	USB Lead (2M A-B Type)		
UP-017	Serial to Ethernet Interface (Moxa)		
01-017			
	Power Supplies		
MXP-549	1.5A 24V EN54-4 PSE & Charger – boxed (7Ah battery)		
MXP-549-12V	1.5A 12V EN54-4 PSE & Charger – boxed (7Ah battery)		
MXP-650	3A 24V EN54-4 PSE & Charger – boxed (17Ah battery)		
MXP-650/D	3A 24V EN54-4 PSE & Charger – boxed (38Ah battery)		
MXP-651	5A 24V EN54-4 PSE & Charger – boxed (17Ah battery)		
MXP-651/D	5A 24V EN54-4 PSE & Charger – boxed (38Ah battery)		
_	Spare (Caged) PSUs		
MXS-049	Spare 1.5A EN54-4 PSU & Battery Charger		
MXS-650	Spare 2.5A EN54-4 PSU & Battery Charger		
MXS-651	Spare 5.0A EN54-4 PSU & Battery Charger		
IWIX5-051	Spare 5.0A ENG4-4 1 50 & Dattery Charger		
	Panel Kits and Spares		
MXS-011	Spare Panel Door Key		
MXS-013	Spare Panel Lock and Key		
MXS-505	Spare Glazed Door key		
MXS-518	MX-5000 Control Panels Spares Kit		
MXS-520	MX-5000 Remote Terminals Spares Kit		
MXS-521	MX-5000 Battery Leads		
MXS-519	MX-5000R Rack Mount Spares Kit		
MXS-522	MX-5000R Battery Leads		
MXS-5-FP-S	Spare Fascia Plate and Membrane		
MXS-5-FP-ML	Spare Fascia Plate and Membrane		
	Spare Base Cards		
MXS-501-CP-S	Spare 5100 Basecard w Small Chassis – Apollo/Hochiki		
MXS-501-CP-M	Spare 5100 Basecard w Med Chassis – Apolio/Hochiki		
MXS-501-PCB	Spare 5100 1 Loop Basecard PCB – no loop cards		
	(programmed)		
MXS-501-PSU	Spare 5100 1 Loop Basecard – PSU only		
MXS-502-CP	Spare 5200 Basecard w Med Chassis – Apollo/Hochiki		
MXS-502-PCB	Spare 5200 1 Loop Basecard PCB – no loop cards		
	(programmed)		
MXS-502-PSU	Spare 5200 1 Loop Basecard – PSU only		
MXS-503-CP	Spare 5400 Basecard w Lrg Chassis – Apollo/Hochiki		
MXS-503-CP-E	Spare 5400 Basecard w Ext Chassis – Apollo/Hochiki		
MXS-503-PCB	Spare 5400 1 Loop Basecard PCB – no loop cards (programmed)		
MXS-503-PSU	Spare 5400 1 Loop Basecard – PSU only		
MXS-504	Spare Display card		
MXS-506	Spare MX-5010 Card only		
MXS-506/FT	Spare MX-5010 Card only – fault-tolerant network		
MXS-507	Spare MX-5020 Card Only		
MXS-507/FT	Spare MX-5020 Card Only – fault-tolerant network		
MXS-508	Spare MX-5030 Card Only		
MXS-508/FT	Spare MX-5030 Card Only – fault-tolerant network		

Product Code	Description	
	Small Enclosure Spares	
MXM-501	Semi-Flushing Bezel	
MXM-522-BB	Spare Back Box	
MXM-522-D1	Spare Door	
MXM-522-CP	Spare Chassis Mtg Plate	
	Madium Englacura Sharaa	
MXM-502	Medium Enclosure Spares Semi-Flushing Bezel – MX-5000	
MXM-508	Glazed Door Kit – medium	
MXM-5087	Glazed Door Kit – medium Glazed Door Kit – medium (double aperture)	
MXM-523-BB	Spare Back Box	
MXM-523-D1	Spare Door	
MXM-523-D1	Spare Door Spare Door (c/w zone aperture)	
MXM-523-CP	· · ·	
IVIXIVI-523-CP	Spare Chassis Mounting Plate	
	Large/Deep Enclosure Spares	
MXM-503	Semi-Flushing Bezel – MX-5000	
MXM-507	Glazed Door Kit – large/deep	
MXM-507Z	Glazed Door Kit – large/deep (double aperture)	
MXM-524-BB	Spare Back Box	
MXM-525-BB	Spare Back Box – deep enclosure	
MXM-524-D1	Spare Door	
MXM-524-D2	Spare Door – c/w zone aperture	
MXM-524-D3	Spare Door – c/w 2 x switch apertures	
MXM-524-D4	Mimic Door with Single Aperture	
MXM-524-D5	Blank Door	
MXM-524-CP	Spare Chassis Mounting Plate	
	Extended Enclosure Spares	
MXM-536	Semi-Flushing Bezel	
MXM-538-D1	Glazed Door Kit – extended (zone aperture)	
MXM-538-D2	Glazed Door Kit – extended (2 x glazed apertures)	
MXM-538-D3	Glazed Door Kit – extended (mimic aperture)	
MXM-537-BB	Spare Back Box	
MXM-537-D1	Spare Door	
MXM-537-D2	Spare Panel Door with Mimic Aperture	
MXM-537-BP	Blank Plate for Zone LED Aperture	
10/04 501	Repeater Enclosure Spares	
MXM-521	Semi-Flushing Bezel – MX-5010 / 5020	
MXM-509	Semi-Flushing Bezel – MX-5030 RCT – large	
MXM-543-BB	Spare back-box – MX-5010 / 5020	
10/04 544 55	Spare back-box – MX-5030 RCT – large	
MXM-544-BB		
MXM-543-D1	Spare panel cover – MX-5010 / 5020	
MXM-543-D1 MXM-543-D2	Spare panel cover – MX-5010 / 5020 Spare panel cover + K/S app – MX-5010 / 5020	
MXM-543-D1	Spare panel cover – MX-5010 / 5020	

Product Code	Description	
	Other Enclosure Spares	
MXM-516	Battery (18Ah) / Utility Enclosure – medium	
MXM-517	Battery (18Ah) / Utility Enclosure – large	
MXM-546	Battery (45Ah) Enclosure – deep	
MXM-518	Utility Enclosure – deep	
MXM-519	Chassis mounting plate for Utility Enclosure (3 cards)	
MXM-531	Document Enclosure – medium	
MXM-532	Document Enclosure – large	
MXM-533	Modem/ESPA/BMS Interface Enclosure	
MXM-504	Termination Enclosure – medium	
MXM-505	Termination Enclosure – large	
MXM-506	Termination Enclosure – deep	
MXM-530	Cable Clamp	
	Small Enclosure Special Finishes	
MXM-501-SSB	Semi-Flushing Bezel – stainless steel brushed	
MXM-522-D1-SSB*	Spare Door – stainless steel brushed	
MXM-522-BB-SSB	Spare Back Box – for use with stainless steel door (MW334E)	
* Add F for fitted		
	Medium Enclosure Special Finishes	
MXM-502-SSB	Semi-Flushing Bezel – stainless steel brushed	
MXM-523-D1-SSB*	Spare Door. Stainless steel brushed	
MXM-523-D1-55B*	Spare Door (c/w Zone Aperture) – stainless steel	
	brushed	
MXM-523-BB-SSB	Spare Back box for use w stainless steel door (MW334E)	
* Add F for fitted		
	Large/Deep Enclosure Special Finishes	
MXM-503-SSB	Semi-Flushing Bezel – stainless steel brushed	
MXM-524-D1-SSB*	Spare Door – stainless steel brushed	
MXM-524-D2-SSB*	Spare Door (c/w Zone Aperture) – stainless steel brushed	
MXM-524-BB-SSB	Spare Back Box – for use with stainless steel door	
* Add F for fitted	(MW334E)	
	Repeater Enclosure Special Finishes	
MXM-521-SSB	Semi-Flushing Bezel – MX-5010/5020 (stainless steel brushed)	
MXM-509-SSB	Semi-Flushing Bezel – MX-5030 Large RCT (stainless steel brushed)	
MXM-543-D1-SSB	Panel Cover – MX-5010/5020 (stainless steel brushed)	
MXM-543-D2-SSB	Panel Cover & Key Switch Aperture – MX-5010/5020 (stainless steel brushed)	
MXM-544-D1-SSB	Panel Cover – MX-5030 Large RCT (stainless steel brushed)	
MXM-544-D2-SSB	Panel Cover & Key Switch Aperture – MX-5030 large RCT (stainless steel brushed)	

Product Code	Description	
	Rack Mount Panels	
MX-5101R	1-Loop Fire Panel – Apollo/Hochiki	
MX-5201R	1-2 Loop Fire Panel c/w 1 Loop Card – Apollo/Hochiki	
MX-5401R	1-4 Loop Fire Panel c/w 1 Loop Card – Apollo/Hochiki	
MX-5101AR	1-Loop Fire Panel - Apollo Core Protocol	
MX-5201AR	1-2 Loop Fire Panel c/w 1 Loop Card – Apollo Core Protocol	
MX-5401AR	1-4 Loop Fire Panel c/w 1 Loop Card – Apollo Core Protocol	
MX-5101VR	1-Loop Fire Panel – Argus	
MX-5201VR	1-2 Loop Fire Panel c/w 1 Loop Card – Argus	
MX-5401VR	1-4 Loop Fire Panel c/w 1 Loop Card – Argus	
MX-5101NR	1-Loop Fire Panel – Nittan	
MX-5201NR	1-2 Loop Fire Panel c/w 1 Loop card – Nittan	
MX-5401NR	1-4 Loop Fire Panel c/w 1 Loop card – Nittan	
	Rack Mount LED Indication	
MXP-513R-050RD	4U LED Card 50 Zone Fire (red)	
MXP-513R-050RY	4U LED Card 50 Zone Fire (red) + Fault (vellow)	
MXP-513R-050YL	4U LED Card 50 Zone Fault (yellow)	
MXP-513R-100RD	4U LED Card 100 Zone Fire (red)	
MXP-513R-100RY	4U LED Card 100 Zone Fire (red) + Fault (yellow)	
MXP-513R-100YL	4U LED Card 100 Zone Fault (yellow)	
MXP-513R-200RY	4U LED Card 200 Zone Fire (red) + Fault (yellow)	
MXP-513R-050CRY	4U LED Card 50 Zone Column Format – Fire (red) +	
MIXI 9191 0300111	Fault (yellow)	
MXP-513R-050CRYG	4U LED Card 50 Zone Column Format (30 x red/yellow and 20 x green/yellow)	
	Deal: Marint Craws	
MXM 510 16U	Rack Mount Spares IP55 19" Rack Mount Enclosure – 16U high	
MXM-510-16U		
MXM-510-20U MXM-510-KL	IP55 19" Rack Mount Enclosure – 20U high	
MXM-510-RL MXM-510-BS	CAM Key-Lock Kit for Outer Door	
MXM-510-BS1	Battery Shelf	
MXM-510-D51	Battery Shelf Lower Chassis Plate	
MXM-511-1U		
MXM-511-10	Blanking Plate – 1U Blanking Plate – 2U	
MXM-511-20		
	Blanking Plate – 3U	
MXM-511-4U	Blanking Plate – 4U	
MXM-511-5U	Blanking Plate – 5U	
MXM-511-6U	Blanking Plate – 6U Blanking Plate – 7U	
MXM-511-7U	Blanking Plate – 70 Blanking Plate – 80	
MXM-511-8U		
MXM-511-9U	Blanking Plate – 9U	
MXM-511-1U-TOP	Blanking Plate – 1U-TOP	
MXM-512	Blanking LED Plate – 4U	
MXM-513-BB	6U Back Box	
MXM-515-6U	6U Chassis Plate	
MVM E12 D1		
MXM-513-D1	6U Door D1 Blank	
MXM-513-D2	6U Door D1 Blank 6U Door D2 LED	
MXM-513-D2 MXM-513-D3	6U Door D1 Blank 6U Door D2 LED 6U Door D1 c/w Aperture	
MXM-513-D2 MXM-513-D3 MXM-513-BP	6U Door D1 Blank 6U Door D2 LED 6U Door D1 c/w Aperture 6U Switch/LED Blank Plate	
MXM-513-D2 MXM-513-D3 MXM-513-BP MXM-513-MF	6U Door D1 Blank 6U Door D2 LED 6U Door D1 c/w Aperture 6U Switch/LED Blank Plate 6U Switch/LED Mounting Frame	
MXM-513-D2 MXM-513-D3 MXM-513-BP MXM-513-MF MXM-513-FP	6U Door D1 Blank 6U Door D2 LED 6U Door D1 c/w Aperture 6U Switch/LED Blank Plate 6U Switch/LED Mounting Frame 6U Fascia Plate Blank	
MXM-513-D2 MXM-513-D3 MXM-513-BP MXM-513-MF MXM-513-FP MXM-514-BB	6U Door D1 Blank 6U Door D2 LED 6U Door D1 c/w Aperture 6U Switch/LED Blank Plate 6U Switch/LED Mounting Frame 6U Fascia Plate Blank 8U Back Box	
MXM-513-D2 MXM-513-D3 MXM-513-BP MXM-513-MF MXM-513-FP MXM-514-BB MXM-515-8U	6U Door D1 Blank 6U Door D2 LED 6U Door D1 c/w Aperture 6U Switch/LED Blank Plate 6U Switch/LED Mounting Frame 6U Fascia Plate Blank 8U Back Box 8U Chassis Plate	
MXM-513-D2 MXM-513-D3 MXM-513-BP MXM-513-MF MXM-513-FP MXM-514-BB MXM-515-8U MXM-514-D1	6U Door D1 Blank 6U Door D2 LED 6U Door D1 c/w Aperture 6U Switch/LED Blank Plate 6U Switch/LED Mounting Frame 6U Fascia Plate Blank 8U Back Box 8U Chassis Plate 8U Door D1 c/w Aperture	
MXM-513-D2 MXM-513-D3 MXM-513-BP MXM-513-MF MXM-513-FP MXM-514-BB MXM-515-8U	6U Door D1 Blank 6U Door D2 LED 6U Door D1 c/w Aperture 6U Switch/LED Blank Plate 6U Switch/LED Mounting Frame 6U Fascia Plate Blank 8U Back Box 8U Chassis Plate	



Technical support

Highly rated customer support. Available by telephone and online.

As an Advanced customer, you have access to a host of helpful advice and support.

This includes a wealth of online information, from 'how to' videos to datasheets and detailed product manuals. Simply complete one of our online forms and you'll be able to access a range of additional services, previously available to those with an Advanced360 account.





Services include:

- **Technical support** available by telephone and online by raising a support ticket, which one of our experienced technical support engineers will answer.
- Training direct customers can book training online and will be sent training certificates by email. If you need to access a previous training certificate, simply complete an online request form. All nondirect customers should book training through their distributor.





• **Software** – download software

packages by installation/site.

Literature - download manuals,

and save your software

specifications, approved partner certificates, technical

information and more.

Warranty – download our warranty statement.

Join us in **Creating a safer future**



To ensure you're getting maximum benefit from all your Advanced products, we offer comprehensive training and support:

- Regular CPDs on:
- False alarm management - BS 8629 evacuation
- alert systems
- Emergency lighting
- Access to in-person and online product training
- 24-hour-access to 'How-to' films covering popular topics

Book your free CPD place



Advanced – made in the UK. Trusted around the world Discover more: advancedco.com | enquiries@advancedco.com | +44 (0)345 894 7000



with **FREE** training and support





Email: enquiries@advancedco.com Web: www.advancedco.com

in Advanced



MxPro 5 and all other Advanced product brands are trademarks of Advanced Electronics Ltd. All rights reserved



SSD5277 UK & Ireland

A Halma company