

## Non-POE 5-Port 10/100/1000 Mbps Switch

Plastic housing



### Features

- 5x 10/100/1000Mbps auto-sensing RJ45 ports (Auto MDI/MDIX).
- Gigabit non-blocking transmission, keeps network fluent.
- Support MAC self learning and updating.
- 10/100/1000Base-T(X) automatic detection, full/half Duplex MDI/MDI-X adaptive

### Specifications

Power Consumption	0.7W. Max power consumption < 6W
Power Input	AC: 100 ~ 240V; 50~60Hz
Power Output	5V/1A
Network Protocol	IEEE802.3, 10BASE-T; IEEE802.3i, 10Base-T; IEEE802.3u, 100Base-TX; IEEE802.3ab, 1000Base-T; IEEE802.3x
Twisted Pair Transmission	10BASE-T: Cat5 UTP (≤100 meter) 100BASE-TX: Cat5 or later UTP (≤100 meter) 1000BASE-T: Cat5 or later UTP (≤100 meter)
Forwarding Mode	Store-and-Forward
Forwarding Rate	7.44Mpps
Back-Bound Bandwidth	10Gbps
Buffer Memory	1M
MAC Address Table	2K
Standard Protocol	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE802.3ab, IEEE802.3z
Operation Temp / Humidity	-20~+55°C / 5%~90% RH non condensing
Storage Temp / Humidity	-40~+75°C / 5%~95% RH non condensing
Dimension	83 x 52 x 22mm
Installation Method	Desktop / Wall mounted / 19-inch 1U cabinet installation
Protection	IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge IEC61000-4-5(Lightning protection/Surge): Power:CM±4kV/DM±2kV; Port: ±4kV